

SAFETY DATA SHEET

Section 1. Product Identification

Product Name: Coarse Grit, Fine Grit Limestone

Other means of identification

SDS number: JAJ 1000

Synonyms: Calcium Carbonate

Recommended use: Agriculture or industrial filler

Recommended Restrictions: Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name: J.A. Jack and Sons, Inc, dba Arcosa Specialty Materials

Address: 5427 Ohio Avenue, South

Seattle, WA 98134

Telephone: (206) 762-7622

Website: ArcosaSpecialtyMaterials.com

Emergency phone number: 1-800-624-5963

Section 2. Hazard(s) Identification

Emergency Overview: These products are not flammable, combustible, or explosive. They do not cause burns or

severe skin or skin irritation. A single exposure will not result in serious adverse health effect. Prolonged contact with any of these products may result in abrasions to the skin or irritation of the eyes. Products are coarsely ground to minimize casual dust. Prolonged

inhalation of the casual dust may irritate the respiratory tract.

Physical hazards: Not classified Health Hazards: Not classified

Acute:

Eyes: May cause mechanical irritation of eyes in rare cases. If burning, redness, itching, pain or

other symptoms persist or develop, consult physician. Eye irritation Category 2, subcategory

2B

Skin: Prolonged contact with the skin may cause irritation. Rubbing of this product against the skin

can result in abrasion. Rinse with water until free of material to avoid abrasion, wash skin

thoroughly with mild soap and water. May dry skin. Mild skin irritation Category B.

Inhalation: Inhalation of casual dust from this product may irritate the nose, throat, lungs, and upper

respiratory tract. Persons exposed to regular amounts of this dust over long periods may be forced to leave area because of nuisance conditions such as coughing, sneezing, and nasal irritation. Labored breathing may occur after excessive long term inhalation. If respiratory

symptoms persist, consult physician.

Chronic: Limestone displays no specific toxic properties.

Environmental hazards: Not Classified OSHA defined hazards: Not Classified

GHS Classification Category 1A

Carcinogenicity:

Label elements:



Signal word: Danger

Hazard statement: Causes eye and skin irritation. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Precautionary statement:

Prevention: Wash hands thoroughly after handling. Wear protective gloves. Avoid breathing dust. Wear

respiratory protection.

SDS ID: JAJ 1000 Revision date: 01 July 2017 Page **1** of **6**



Response: If eye irritation persists, if skin irritation occurs, or if experiencing respiratory sympt		
	medical advice/attention.	
Storage:	Store as indicated in Section 7.	
Disposal:	Dispose of in accordance with local, state, and federal regulations.	
Potential Health Effects	Group 1: Carcinogenic to humans – Quartz (SiO2) CAS# 14808-60-7	
Carcinogenicity IARC:		
NPT:	The NPT report on carcinogens lists crystalline silica (respirable size – passing 10	

T: The NPT report on carcinogens lists crystalline silica (respirable size – passing 10 microns) as a known human carcinogen. Respirable particles in these products is not anticipated

Section 3. Composition/Information on Ingredients Substance / Mixture: Substance			
Limestone	1317-65-3	98-100	
Silicon Dioxide (Crystalline Silica)	14808-60-7	>0.1%	

The specific identity and/or exact concentration has been withheld as a trade secret.

	Section 4. First-Aid Measures			
Inhalation:	If irritation develops, remove to fresh air. Get medical attention if irritation persists.			
Skin:	First aid is not normally required. Wash skin with soap and water. Get medical attention if			
	irritation develops or persists. Remove contaminated clothing and launder before reuse.			
Eye contact:	Flush with plenty of water, holding the eyelids apart to ensure through washing. Get medical			
	attention if irritation persists.			
Ingestion:	Rinse mouth with water. Do not induce vomiting unless directed to do so by medical			
	personnel. Get medical attention if large amount is swallowed.			
Most Important	Long exposure to casual dust may cause mechanical eye and skin irritation. Inhalation of			
symptoms/effects, acute	dust may cause respiratory irritation, coughing and difficulty in breathing.			
and delayed:				
Indication of Immediate	None required under normal conditions of use.			
medical attention and				
special treatment needed:				

Section 5. Fire and Explosion Hazard Data			
Flash Point:	Non-Flammable		
Suitable (and unsuitable) extinguishing	Use media appropriate for the surrounding fire.		
media:			
Specific hazards arising from the	Not flammable or combustible.		
chemical:			
Special protective equipment and	Firefighters should wear positive pressure self-contained breathing		
precautions for fire-fighters:	apparatus and full protective clothing.		

Section 6. Accidental Release Measures

Personal precautions, protective wear appropriate protective equipment. Avoid creating and breathing dust. equipment, and emergency procedures

SDS ID: JAJ 1000 Revision date: 01 July 2017 Page 2 of 6



Report releases as required by local and federal authorities **Environmental hazards**

Methods and materials for containment and cleaning up:

Collect and place in appropriate container for use or disposal.

Section 7. Handling and Storage			
Environmental	No special environmental precautions required.		
precautions:			
Precautions for safe	Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wear protective clothing		
handling:	and equipment as described in Section 8. Wash with soap and water after use.		
Conditions for safe	Store in a cool, dry, well-ventilated area. Protect from physical damage. Do not store near		
storage, including any	acids		
incompatibilities:			

Section 8. Exposure Controls/Personal Protection			
Exposure guidelines:			
Limestone – CAS # - 1317-65-3	5 mg/m3 TWA OSHA PEL (respirable)		
	10 mg/m3 TWA OSHA PEL (total dust)		
Crystalline Silica – CAS # - 14808-60-7	10 mg/m3 TWA OSHA PEL (respirable fraction) % Silica + 2		
	30 mg/m3 TWA OSHA PEL (total dust) % Silica + 2		
	0.025 mg/m3 TWA ACGIH TLV (respirable fraction)		
Appropriate engineering controls			
Engineering Controls:	Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits.		
Individual protection measures, such as personal protective equipment:			
Respiratory protection:	If the exposure limits are exceeded a NIOSH approved particulate respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 or other applicable regulations and good industrial hygiene practice.		
Skin protection:			
Eye protection:			
Hygiene measures:			
Other:	ther: None required.		

Section 9. Physical and Chemical Properties				
Appearance Gray grains				
Odor	Odorless			
Reactive Will react with most acid to release heat and carbon dioxide gruntil neutral pH is restored.				
Odor threshold: Not applicable	pH: Not applicable			
Melting Point/Freezing Point: 2372°F /1300°C	Boiling point: Not applicable			
Flash point: Not applicable	Evaporation rate: Not applicable			
Flammability (solid, gas):				
Flammable limits: LEL: Not applicable	UEL: Not applicable			
Vapor pressure: Not applicable	Vapor density: Not applicable			
Relative density: 87-107 lb./ft ³	Solubility in Water: 0.0006%			

SDS ID: JAJ 1000 Revision date: 01 July 2017 Page 3 of 6



Partition coefficient: n-octanol /water: Not Auto-ignition temperature: Not applicable

applicable

Decomposition Temperature: over 1112°F / 600°C Viscosity: Not applicable

Section 10. Chemical Stability and Reactivity			
Reactivity: Reacts with acids.			
Chemical stability:	Stable under normal conditions.		
Possibility of hazardous reactions:	Reacts with acids to form carbon dioxide and heat		
Conditions to avoid:	None known		
Incompatible materials:	Avoid acids, alum, ammonium salts, mercury and heat, fluorine and magnesium		
Hazardous decomposition products:	Thermal decomposition may produce oxides of carbon and calcium. This displaces the oxygen in the air in enclosed spaces (danger of suffocation).		

	Section 11. Toxicological Information		
Likely routes of exposure			
Inhalation:	Inhalation of dust may cause irritation to the nose, throat and upper respiratory tract		
	with coughing and shortness of breath.		
Ingestion:	n: Not expected to cause adverse effects.		
Skin contact:	: Prolonged skin contact may cause mechanical irritation and abrasions		
Eye contact:	tact: May cause mechanical irritation with redness, tearing and pain		
Chronic effects: None known			
Germ Cell Mutagenicity: This product is not expected to cause germ cell mutagenicity			
Developmental / Reproductive	This product is not expected to cause adverse effects on reproduction or		
Toxicity: development			
Carcinogenicity:	Crystalline silica quartz is listed as "Carcinogenic to Humans" (Group 1) by IARC		
	and "Known to be a Human Carcinogen" by NTP. The crystalline silica in this		
	product is inextricably bound in large grains so that no exposure occurs during		
	normal use and handling. Therefore this product is not classified as a carcinogen.		
None of the other components are listed as a carcinogen by IARC, NTP or OSI			

Acute Toxicity Values:

Limestone: Oral rat LD50 >5000 mg/kg
Crystalline Silica, Quartz: Oral rat LD50 >5000 mg/kg

Section 12. Ecological Information

In solid state, these minerals are a major part of the rocks of the earth's surface. In these products the grains are not easily suspended in water to support a dangerous concentration for wildlife. They are partially dissolved in a natural state and indispensable part of the natural waters. These minerals are not biodegradable. Negative effects on the environment should therefore be excluded. Restrictions may be indicated that concentrated suspensions of these minerals in natural waters may have an unfavorable effect on water organisms (disturbance of the micro flora and fauna in the sediment and subsequent detriment to the existence of higher water organisms).

Product:

. roddot:	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and	ED50 (Daphnia magna (Water flea)): >1,000 mg/l aquatic invertebrates
other	Exposure time: 48 h
Toxicity to algae	ED50 (Desmodesmus subspicatus (green algae)): >200 mg/l
	Exposure time: 72 h

Ingredients: Limestone:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 10,000 mg/l Exposure time: 96 h

SDS ID: JAJ 1000 Revision date: 01 July 2017 Page 4 of 6



Toxicity to daphnia and ED50 (Daphnia magna (Water flea)): >1,000 mg/l aquatic invertebrates

other Exposure time: 48 h

Toxicity to algae ED50 (Desmodesmus subspicatus (green algae)): >200 mg/l

Exposure time: 72 h

Persistence and degradability

Product:

Biodegradability Not applicable

Bio-accumulative potential

Ingredients:

Limestone: Partition coefficient: n-octanol/water Not applicable

Mobility in soil: No data available

Other adverse effects

Product:

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA

Section 602 Class I Substances. This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Sub

part. A, APP. A+B)

Ingredients: Limestone:

Results of PBT and vPvB: Non-classified PBT substance, Non-classified vPvB substance assessment

Section 13 Disposal Considerations

Disposal procedure: Dispose in accordance with all local, state and federal regulations.

Section 14. Transport Information					
	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT		Not Regulated			
TDG		Not Regulated			
IMDG		Not Regulated			
IATA		Not Regulated			
		Not Regulated			

Transport in bulk (according to Annex II of Not applicable MARPOL 73/78 and the IBC Code):

Special precautions: None known.

Safety, health, and environmental regulations specific for the product in question.

Section 15 Regulatory Information		
CERCLA Section 103:	This product is not subject to CERCLA spill reporting requirements. Many states	
	have more stringent release reporting requirements. Report spills required under	
	federal, state and local regulations.	
SARA Hazard Category (311/312):	Not hazardous	
EPA SARA 313:	This Product Contains the Following Chemicals Subject to Annual Release	
	Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None	
US TSCA:	US TSCA: All of the components of this material are listed on the Toxic Substances Con	
	Act (TSCA) Chemical Substances Inventory or are exempt.	
Clean Air Act:	This product does not contain any hazardous air pollutants (HAP), as defined by	
	the U.S. Clean Air Act Section 12 (40 CFR 61). This Product does not contain any	

SDS ID: JAJ 1000 Revision date: 01 July 2017 Page **5** of **6**



chemicals listed under the U.S. Clean Air Act Section 112® for Accidental Release Prevention (40 CFR 68.130, Subpart F) This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489

Clean Water Act:

This product does not contain any Hazardous Substances listed under the U.S. Clean Water Act, Section 311, Table 116.4A This product does not contain any Hazardous Chemicals listed under the U.S. Clean Water Act, Section 311, Table 117.3 This Product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

California Proposition 65:

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity:

Crystalline Silica, quartz* / 14808-60-7 / 0.1-1.9% / Cancer

CANADA

Canadian CEPA: All of the components are listed on the Canadian DSL or are exempt


Canadian WHMIS: Not a controlled product

This product has been classified in accordance with the hazard criteria in the CPR and the MSDS contains all the information required by the CPR.

Section16 Other Information				
NFPA Rating:	Health = 1	Flammability = 0	Instability = 0	
HMIS Rating:	Health = 1	Flammability = 0	Physical Hazard = 0	

NFPA ratings

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe





Disclaimer This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS Revision History: All Section revised - Update to GHS format

Date of preparation: July 1, 2017

Date of last revision: None

SDS ID: JAJ 1000 Revision date: 01 July 2017 Page 6 of 6