

SAFETY DATA SHEET

	Section 1. Product Identification
Product N	
ther means of identificatio	
SDS nun	
Synon	
Recommended	
Recommended Restrict	ions: Use in accordance with manufacturer's recommendations.
anufacturer/Importer/Supp	blier/Distributor information
Company n	ame: J.A. Jack and Sons, Inc, dba Arcosa Specialty Materials
Add	ress: 5427 Ohio Avenue, South
	Seattle, WA 98134
Teleph	
	osite: www. ArcosaSpecialtyMaterials.com
Emergency phone nur	nber: 1-800-624-5963
	Section 2. Hazard(s) Identification
Emergency Overview:	These products are not flammable, combustible, or explosive. They do not cause burns o
	severe skin or skin irritation. A single exposure will not result in serious adverse health effect
	Prolonged contact with any of these products may result in abrasions to the skin or irritation
	of the eyes. Prolonged inhalation of the dust may irritate the respiratory tract.
Physical hazards:	Not classified
Health Hazards:	Not classified
Acute:	
Eyes:	May cause mechanical irritation of eyes in rare cases. If burning, redness, itching, pain o
	other symptoms persist or develop, consult physician. Eye irritation Category 2, subcategory
01.12	2B.
Skin:	Prolonged contact with the skin may cause irritation. Rubbing of this product against the skin
	can result in abrasion. Rinse with water until free of material to avoid abrasion, wash skir
Inholotion	thoroughly with mild soap and water. May dry skin. Mild skin irritation Category B.
Inhalation:	Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer. Silicosis increases the risk of tuberculosis. Studies
	have shown various autoimmune and chronic kidney diseases in workers exposed to
	respirable crystalline silica. Some studies show and increased incidence of chronic
Chronice	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica.
Chronic:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure
Chronic:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer
Chronic:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and
Chronic:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in workers exposed to respirable crystalline silica. Some studies
Chronic:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in workers exposed to respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to
	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in workers exposed to respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica.
Environmental hazards:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in workers exposed to respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica.
Environmental hazards: OSHA defined hazards:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in workers exposed to respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Not Classified Not Classified
Environmental hazards:	respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica. Limestone displays no specific toxic properties. Inhalation prolonged and repeated exposure to respirable crystalline silica can result in lung disease (i.e. silicosis) and lung cancer Silicosis increases the risk of tuberculosis. Studies have shown various autoimmune and chronic kidney diseases in workers exposed to respirable crystalline silica. Some studies show and increased incidence of chronic bronchitis and emphysema in workers exposed to crystalline silica.



Label elements:



Danger	
Causes eye and skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Wash hands thoroughly after handling. Wear protective gloves. Avoid breathing dust. Wear	
respiratory protection.	
If eye irritation persists, if skin irritation occurs, or if experiencing respiratory symptoms: Get	
medical advice/attention.	
Store as indicated in Section 7.	
Disposal: Dispose of in accordance with local, state, and federal regulations.	
Group 1: Carcinogenic to humans – Quartz (SiO2) CAS# 14808-60-7	
Carcinogenicity IARC:	
The NPT report on carcinogens lists crystalline silica (respirable size – passing 10	
microns) as a known human carcinogen. Respirable particles in these products is not anticipated.	

Section 3. Composition/Information on Ingredients Substance / Mixture: Substance		
Limestone	1317-65-3	98-100
Silicon Dioxide (Crystalline Silica)	14808-60-7	>0.1%

The specific identity and/or exact concentration has been withheld as a trade secret.

Section 4. First-Aid Measures		
Inhalation:	If irritation develops, remove to fresh air. Get medical attention if irritation persists.	
Skin:	First aid is not normally required. Wash skin with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before reuse.	
Eye contact:		
Ingestion:	Rinse mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if large amount is swallowed.	
Most Important symptoms/effects, acute and delayed:	cute dust may cause respiratory irritation, coughing and difficulty in breathing.	
Indication of Immediate medical attention and special treatment needed:	None required under normal conditions of use.	



Section 5. Fire and Explosion Hazard Data	
Flash Point:	Non-Flammable
Suitable (and unsuitable) extinguishing	Use media appropriate for the surrounding fire.
media:	
Specific hazards arising from the	Not flammable or combustible.
chemical:	
Special protective equipment and	Firefighters should wear positive pressure self-contained breathing
precautions for fire-fighters:	apparatus and full protective clothing.

Section 6. Accidental Release Measures

	Personal precautions, protective	Wear appropriate protective equipment. Avoid creating and breathing dust.
	equipment, and emergency	
	procedures	
_	Environmental hazards	Report releases as required by local and federal authorities.
_	Methods and materials for	Collect and place in appropriate container for use or disposal.
	containment and cleaning up:	

Section 7. Handling and Storage		
Environmental No special environmental precautions required.		
precautions:		
Precautions for safe	Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wear protective clothing	
handling:	and equipment as described in Section 8. Wash with soap and water after use.	
Conditions for safe	Store in a cool, dry, well-ventilated area. Protect from physical damage. Do not store near	
storage, including any	acids.	
incompatibilities:		

Section	on 8. Exposure Controls/Personal Protection	
Exposure guidelines:		
Limestone – CAS # - 1317-65-3	5 mg/m3 TWA OSHA PEL (respirable)	
	10 mg/m3 TWA OSHA PEL (total dust)	
Crystalline Silica – CAS # - 14808-60-	10 mg/m3 TWA OSHA PEL (respirable fraction)	
7	% Silica + 2	
	<u>30 mg/m3</u> TWA OSHA PEL (total dust)	
	% Silica + 2	
	0.025 mg/m3 TWA ACGIH TLV (respirable fraction)	
Appropriate engineering controls		
Engineering Controls:	Use with adequate general or local exhaust ventilation to maintain exposures	
	below the occupational exposure limits.	
Individual protection measures,		
such as personal protective		
equipment:		
Respiratory protection:	If the exposure limits are exceeded a NIOSH approved particulate respirator	
	appropriate for the form and concentration of the contaminants should be used.	
	Selection and use of respiratory equipment must be in accordance with OSHA	
	1910.134 or other applicable regulations and good industrial hygiene practice.	
Skin protection:	Abrasive resistant gloves are recommended if needed to avoid skin contact.	
Eye protection:	Chemical safety glasses with side-shields are recommended.	



Hygiene measures:	Follow general industrial hygiene practices.
Other:	None required.

Section 9. Physic	cal and Chemical Properties
Appearance	White Powder
Odor	Odorless
Reactive	Will react with most acid to release heat and carbon dioxide gas
	until neutral pH is restored.
Odor threshold: Not applicable	pH: Not applicable
Melting Point/Freezing Point: 2372°F /1300°C	Boiling point: Not applicable
Flash point: Not applicable	Evaporation rate: Not applicable
Flammability (solid, gas):	
Flammable limits: LEL: Not applicable	UEL: Not applicable
Vapor pressure: Not applicable	Vapor density: Not applicable
Relative density: 87-107 lb./ft3	Solubility in Water: 0.0006%
Partition coefficient: n-octanol/water: Not applicable	Auto-ignition temperature: Not applicable
Decomposition Temperature: over 1112°F / 600°C	Viscosity: Not applicable

Section 10. Chemical Stability and Reactivity		
Reactivity: Reacts with acids.		
Chemical stability:	Stable under normal conditions.	
Possibility of hazardous reactions:	Reacts with acids to form carbon dioxide and heat.	
Conditions to avoid:	None known	
Incompatible materials: Avoid acids, alum, ammonium salts, mercury and heat, fluorine and magnesiun		
Hazardous decompositionThermal decomposition may produce oxides of carbon and calcium. Thisproducts:displaces the oxygen in the air in enclosed spaces (danger of suffocation)		

Section 11. Toxicological Information

Likely routes of exposure		
Inhalation:	n: Inhalation of dust may cause irritation to the nose, throat and upper respiratory tract	
	with coughing and shortness of breath.	
Ingestion:	Not expected to cause adverse effects.	
Skin contact:	Prolonged skin contact may cause mechanical irritation and abrasions.	
Eye contact:	May cause mechanical irritation with redness, tearing and pain.	
Chronic effects:	: None known	
Germ Cell Mutagenicity:	ity: This product is not expected to cause germ cell mutagenicity.	
Developmental / Reproductive	This product is not expected to cause adverse effects on reproduction or	
Toxicity:	development.	
Carcinogenicity:	Crystalline silica quartz is listed as "Carcinogenic to Humans" (Group 1) by IARC and "Known to be a Human Carcinogen" by NTP. The crystalline silica in this product is inextricably bound in large grains that no exposure occurs during normal use and handling. Therefore this product is not classified as a carcinogen. None of the other components are listed as a carcinogen by IARC, NTP or OSHA.	

Acute Toxicity Values:

Limestone:	Oral rat LD50 >5000 mg/kg	
Crystalline Silica, Quartz:	Oral rat LD50 >5000 mg/kg	



Feetewieitu	Section 12. Ecological Information
Ecotoxicity	In solid state, these minerals are a major part of the rocks of the earth's surface. They are dissolved in a natural state and indispensable part of the natural waters. These minerals are
	not biodegradable. Negative effects on the environment should therefore be excluded
	Restrictions may be indicated that concentrated suspensions of these minerals in natura
	waters may have an unfavorable effect on water organisms (disturbance of the micro flora and
	fauna in the sediment and subsequent detriment to the existence of higher water organisms)
Product:	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and	ED50 (Daphnia magna (Water flea)): >1,000 mg/l aquatic invertebrates
other	Exposure time: 48 h
Toxicity to algae	ED50 (Desmodesmus subspicatus (green algae)): >200 mg/l
	Exposure time: 72 h
Ingredients: Limestone:	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and	ED50 (Daphnia magna (Water flea)): >1,000 mg/l aquatic invertebrates
other	Exposure time: 48 h
Toxicity to algae	ED50 (Desmodesmus subspicatus (green algae)): >200 mg/l
TONICITY TO algae	LDSU (Desinouesinus subspicatus (green algae)). >200 mg/i
TOXICITY TO algae	Exposure time: 72 h
, ,	Exposure time: 72 h
Persistence and degradab	Exposure time: 72 h
Persistence and degradab Product:	Exposure time: 72 h
Persistence and degradab	Exposure time: 72 h
Persistence and degradab Product: Biodegradability	Exposure time: 72 h ility Not applicable
Persistence and degradab Product:	Exposure time: 72 h ility Not applicable
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone:	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable.
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients:	Exposure time: 72 h ility Not applicable
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil:	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable.
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable.
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects Product:	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable. No data available.
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable. No data available. 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects Product:	Exposure time: 72 h
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects Product:	Exposure time: 72 h
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects Product: Regulation:	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable. No data available. 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class I Substances. This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subp
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects Product: Regulation: Ingredients: Limestone:	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable. No data available. 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class I Substances. This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpl A, APP. A+B).
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects Product: Regulation:	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable. No data available. 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class I Substances. This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subp
Persistence and degradab Product: Biodegradability Bio-accumulative potentia Ingredients: Limestone: Mobility in soil: Other adverse effects Product: Regulation: Ingredients: Limestone:	Exposure time: 72 h ility Not applicable Partition coefficient: n-octanol/water - Not applicable. No data available. 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class I Substances. This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subp A, APP. A+B).

Section 13 Disposal ConsiderationsDisposal procedure:Dispose in accordance with all local, state and federal regulations.

Section 14. Transport Information					
	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT		Not Regulated			
TDG		Not Regulated			
IMDG		Not Regulated			



ΙΑΤΑ	Not Regulated		
	Not Regulated		

Transport in bulk (according to Annex II of Not applicable

MARPOL 73/78 and the IBC Code):

Special precautions: None known.

Safety, health, and environmental regulations specific for the product in question.

	Section 15 Regulatory Information
CERCLA Section 103:	This product is not subject to CERCLA spill reporting requirements. Many states
	have more stringent release reporting requirements. Report spills required under
	federal, state and local regulations.
SARA Hazard Category (311/312):	Not hazardous
EPA SARA 313:	This Product Contains the Following Chemicals Subject to Annual Release
	Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None
US TSCA:	All of the components of this material are listed on the Toxic Substances Control
	Act (TSCA) Chemical Substances Inventory or are exempt.
Clean Air Act:	This product does not contain any hazardous air pollutants (HAP), as defined by
	the U.S. Clean Air Act Section 12 (40 CFR 61). This Product does not contain any
	chemicals listed under the U.S. Clean Air Act Section 112® for Accidental Release
	Prevention (40 CFR 68.130, Subpart F) This product does not contain any
	chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or
	Final VOC's (40 CFR 60.489.
Clean Water Act:	This product does not contain any Hazardous Substances listed under the U.S.
	Clean Water Act, Section 311, Table 116.4A This product does not contain any
	Hazardous Chemicals listed under the U.S. Clean Water Act, Section 311, Table
	117.3 This Product does not contain any toxic pollutants listed under the U.S. Clean
	Water Act Section 307.
California Proposition 65:	This product contains the following chemicals known to the State of California to
•	cause cancer or reproductive toxicity:
	Crystalline Silica, quartz / 14808-60-7 / 0.1-1.9% / Cancer
	, , ,
CANADA	

CANADA


 Canadian CEPA:
 All of the components are listed on the Canadian DSL or are exempt


 Canadian WHMIS:
 Not a controlled product

This product has been classified in accordance with the hazard criteria in the CPR and the MSDS contains all the information required by the CPR.

Section16 Other Information			
NFPA Rating:	Health = 1	Flammability = 0	Instability = 0
HMIS Rating:	Health = 1	Flammability = 0	Physical Hazard = 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe





HMIS	
HEALTH	1
FLAMMABILITY	0
INSTABILITY	0
SPECIFIC	0



Disclaimer This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS Revision History:	All Section revised - Update to GHS format
Date of preparation:	July 1, 2017
Date of last revision:	None